

### General

Display Type	Flat panel display / TFT active matrix
Width	40.5 cm
Depth	19.9 cm
Height	38 cm
Weight	3.4 kg
Enclosure Colour	Black, silver

### Display

Diagonal Size	17" - widescreen
Dot Pitch / Pixel Pitch	0.255 mm
Max Resolution	1440 x 900
Colour support	Up to 16.2 million colors
Response Time	8 ms
Display Positions Adjustments	Tilt
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese, Korean
Display Screen Coating	Anti-glare
Tilt Angle	20
Signal Input	VGA

### Image

Image Colour Temperature	9300K, adjustable, 6500K
Image Brightness	250 cd/m <sup>2</sup>
Image Contrast Ratio	500:1
Image Max H-View Angle	140
Image Max V-View Angle	130

### Video Input

Analogue video Signal	RGB
-----------------------	-----

### Expansion / Connectivity

Interfaces	1 x VGA - 15 pin HD D-Sub (HD-15)
------------	-----------------------------------

### Miscellaneous

Cables Included	1 x VGA cable
Flat Panel Mount Interface	100 x 100 mm
Features	Security lock slot (cable lock sold separately)
Compliant Standards	CE, MPR II, UL, TUV, BSMI, GOST, cUL, CB, FCC

### Power

Form Factor	Internal
Voltage Required	AC 120/230 V ( 50/60 Hz )
Power Consumption Operational	28 Watt

### Software / System Requirements

Software Included	Driver
-------------------	--------

### Environmental Standards

EPA Energy Star	Yes
-----------------	-----



Serving Business & Personal Clients

Compliant

**Manufacturer Warranty**

Service & Support	3 years warranty
Service & Support Details	Limited warranty - 3 years

**Environmental Parameters**

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 85%